8500W

DC BATTERY BACKUP WALL MOUNT WI-FI® GARAGE DOOR OPENER

The ultimate garage access solution, designed to optimize space.

KEY FEATURES

SPACE-SAVING
Design Maximizes Versatility

HEAVY LIFTING
Powers 850 lbs. Doors†

WI-FI
Built In

LED LIGHT
Mounts Anywhere

BATTERY BACKUP
CALIFORNIA SB-969 COMPLIANT

myQ integrates with leading smart home platforms. Visit myQ.com to learn more.

SMART

SPACE-SAVING DESIGN OPENS UP THE CEILING.

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

myQ REMOTE LED LIGHT PROVIDES BRIGHT, MAINTENANCE-FREE ILLUMINATION.

INCLUDED AUTOMATIC GARAGE DOOR LOCK MAKES THE GARAGE DOOR VIRTUALLY IMPENETRABLE.

myQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.**

QUIET AND RELIABLE

WALL-MOUNT DESIGN AND QUIET DC MOTOR ELIMINATE NOISE AND VIBRATIONS THROUGH THE CEILING AND PROVIDE SMOOTH OPERATION.

HEAVY-LIFTING POWER OPERATES DOORS UP TO 850 LBS.

INTEGRATED BATTERY BACKUP ENSURES ACCESS EVEN WHEN THE POWER'S OUT.

WARRANTY LIFETIME MOTOR, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

SECURE

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

SECURITY+ 2.0® SENDS A NEW CODE WITH EVERY REMOTE CLICK.

MOTION DETECTOR AUTOMATICALLY TURNS ON THE LIGHT.

THE PROTECTOR SYSTEM® AUTO-REVERSES THE DOOR IF THERE'S AN OBSTRUCTION.

*Linking your myQ account to a partner may require an additional accessory purchase or subscription fee.
**myQ Remote LED Light must be installed to enable use of Timer-to-Close or myQ smartphone control of the garage door. See User Guide for additional information.
†Battery Backup must be installed. Must use 15" or greater radius track. Door must be properly balanced. Smartphone not included.

INCLUDED ACCESSORIES:

myQ REMOTE LED LIGHT — 827LM
Operates automatically with the opener and works with the myQ App.

INTEGRATED BATTERY BACKUP — 485LM
Powers up the opener when the power's out.

AUTOMATIC GARAGE DOOR LOCK — 841LM
Deadbolts the garage door automatically every time it closes.

SMART CONTROL PANEL® — 880LMW
LCD display enables simple programming and adjustment of settings.

3-BUTTON REMOTE CONTROL — 893MAX
Operates up to 3 openers.

POWERFUL ADD-ONS:

MINI UNIVERSAL REMOTE CONTROL — 374UT
Compact and portable to provide quick, easy garage access.

WIRELESS KEYLESS ENTRY — 878MAX
Provides convenient, secure access from outside the garage with a 4-digit PIN.

PRODUCT GUIDE 8500W
DC BATTERY BACKUP WALL MOUNT WI-FI GARAGE DOOR OPENER

LiftMaster®

8500W

DC BATTERY BACKUP WALL MOUNT
WI-FI® GARAGE DOOR OPENER

MASTERFUL ENGINEERING.

MOTOR

- Heavy-Duty 12V DC
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 1.5A Current Rating
- UL® Listed
- 6' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis and Plastic Cover**
- **Internal Chain and Sprocket Drive Mechanism** (63:1 Gear Reduction)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCRJWF)
- **2 Lock Terminals** Allow Another Lock to Be Added for Extra Security (2 Max.)

DIMENSIONS

Max. Door Height: 14 ft.
Max. Door Width: 18 ft.

Headroom Clearance Required: 3 in. from Center of Torsion Bar

MAX. DOOR WEIGHT

850 lbs.†

SPEED

8.5" Per second for door to move upward

7.6" Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -31°F to 149°F

3-Button Remote Control (893MAX)
- Remote Controls: Security+ 2.0
- Keyless entry: Security+ 2.0
- Anti-Burglary Coding

Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Smart Control Panel® (880LMW)
- Timer-to-Close
- Program Remote Controls, Keypads and myQ Accessories
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

myQ® RADIO

902–928 MHz
50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and myQ accessories.
- Enables monitoring and control of garage door openers via smartphone or tablet.**

**myQ Remote LED Light must be installed to enable use of Timer-to-Close or myQ smartphone control of the garage door. See User Guide for additional information.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)**

***May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING

myQ REMOTE LED LIGHT (827LM)

1,500 LM

- Multiple Programming Options, Including myQ App Control
- Mounts to Ceiling or Wall
- Easy-to-Clean Hinged Cover

SHIPPING.

SHIPPING WEIGHT (in lbs.)

38 CARTON

CARTONS (1)

CARTON 1: 27.88" x 11.61" x 9.79"
- Garage Door Opener Head (8500W)
- Smart Control Panel (880LMW)
- 3-Button Remote Control (893MAX)
- The Protector System® Safety Reversing Sensors
- Battery (485LM)
- Automatic Garage Door Lock (841LM)
- myQ Remote LED Light (827LM)

SAFETY AND SECURITY.

- Automatic Garage Door Lock Included (2 Max.)
- Alert-2-Close/Unattended Close Operation††
- Motion Detection Feature on Control Panel
- Hands-Free Work Lights On
- Emergency/Quick Release
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 myQ Devices

†Battery Backup must be installed. Must use 15" or greater radius track. Door must be properly balanced.
††Note: to reduce the risk of injury to persons, only use Alert-2-Close/Unattended Close Operation features when installed with a sectional door.

©2022 Chamberlain Group LLC. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ® and the myQ® logo are registered trademarks of The Chamberlain Group LLC.
300 Windsor Drive, Oak Brook, IL 60523
LiftMaster.com
Wi-Fi® is a registered trademark of Wi-Fi Alliance
UL® and the UL logo are trademarks of UL LLC © 2022 All Rights Reserved.
LMGDENPG8500W_ 202201_MC21

LiftMaster